
REVISION					
ZONE	REV	DESCRIPTION	DATE	CHANGED BY	APPROVED
	F	ECO-15937	09/28/2026	DMAY	GUTTADAURO



CABLE CONSTRUCTION:		NOM DIA:
CONDUCTOR: 24 AWG 7/32 STRANDED TINNED COPPER:		.024 [0.61]
INSULATION: HIGH DENSITY POLYETHYLENE, NOM WALL THICKNESS:		.038 [0.97] .007 [0.17]
PAIRS:	COLOR CODED SINGLES TWISTED INTO PAIRS	.076 [1.93]
CABLE:	(4) TWISTED PAIRS TWISTED TOGETHER TO FORM A CABLE CORE:	.163 [4.14]
JACKET:	POLYVINYLCHLORIDE (PVC), WHITE, NOM WALL THICKNESS (PRESSURE): OVERALL CABLE DIAMETER	 .026 [0.66] .215 ± .010 [5.46 ± 0.25] (BY PI TAPE)

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED. THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

UNLESS OTHERWISE SPECIFIED
LEADING DIMENSIONS ARE INCHES
DIMENSIONS IN [ ] ARE MILLIMETERS

TOLERANCES:

.X = ±.2 [5]	FRACTIONS
.XX = ±.02 [0.5]	± 1/32
.XXX = ±.005 [0.13]	ANGLES ± 1°

CABLE LENGTH TOLERANCES:
≤12 [305] = +1 [25] / -0
>12 [305] ≤ 60 [1524] = +2 [51] / -0
>60 [1524] ≤ 120 [3048] = +4 [102] / -0
>120 [3048] ≤ 300 [7620] = +6 [152] / -0
>300 [7620] = +5% / -0
CABLE LENGTH TOL IAW IPC A-620

ALL DIMENSIONS ARE FOR REFERENCE ONLY AND SUBJECT TO CHANGE WITHOUT NOTICE.
UN-DIMENSIONED/NON-CRITICAL FEATURES MAY VARY IN SIZE AND LOCATION
COLORS MAY VARY

L-com®
an INFINITE company
Website: www.L-com.com
Phone: 1.800.341.5266 | 1.978.682.6936

INTERPRET ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5

SCALE	SHEET
NONE	1 OF 1

DESCRIPTION: C5E UTP 4PR/24 STR PVC WHT 1K

SIZE	CAGE CODE	DRAWN BY	ITEM NO.	REV
A	43321	DMAY	TC2593	F

LC DS Rev-E Asize