
REVISION					
ZONE	REV	DESCRIPTION	DATE	CHANGED BY	APPROVED
	G	ECO-15966	07/01/2026	HBAKKE	DWANG



DESCRIPTION	DIAMETER	MATERIAL
INNER CONDUCTOR	Ø.108±.002 [2.74±0.05]	BARE COPPER STRANDED
INSULATION	Ø.285±.008 [7.24±0.20]	FOAM PE
FIRST SHIELD	-	BONDED ALUMINUM (AL/PET/AL)
SECOND SHIELD	Ø.320 [8.13]	TINNED COPPER WIRE
OUTER JACKET	Ø.400±.008 [10.16±0.20]	BLACK TPU

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED. THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

UNLESS OTHERWISE SPECIFIED
LEADING DIMENSIONS ARE INCHES
DIMENSIONS IN [ ] ARE MILLIMETERS

TOLERANCES:

.X = ±.2 [5]	FRACTIONS
.XX = ±.02 [0.5]	± 1/32
.XXX = ±.005 [0.13]	ANGLES ± 1°

CABLE LENGTH TOLERANCES:
≤12 [305] = +1 [25] / -0
>12 [305] ≤ 60 [1524] = +2 [51] / -0
>60 [1524] ≤ 120 [3048] = +4 [102] / -0
>120 [3048] ≤ 300 [7620] = +6 [152] / -0
>300 [7620] = +5% / -0
CABLE LENGTH TOL IAW IPC A-620

ALL DIMENSIONS ARE FOR REFERENCE ONLY AND SUBJECT TO CHANGE WITHOUT NOTICE.
UN-DIMENSIONED/NON-CRITICAL FEATURES MAY VARY IN SIZE AND LOCATION
COLORS MAY VARY

L-com®
an INFINITE company
Website: www.L-com.com
Phone: 1.800.341.5266 | 1.978.682.6936

INTERPRET ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5

SCALE	SHEET
NONE	1 OF 1

DESCRIPTION
CA-400UF ULTRA FLEX SERIES LOW LOSS COAXIAL CABLE

SIZE	CAGE CODE	DRAWN BY	ITEM NO.	REV
A	43321	D.FRISIELLO	CA-400UF	G